

MULTIMESSAGE TRAILER

Sequence Trailer

Code: RE-MUL



FEATURES

- **Tow** manufactured in 16-gauge galvanized sheet, 1/2"x1/8" angle and 2.5" SHS with primary recovering in yellow enamel.
- Leaf spring suspension system, axle support of 1,500 lbs and a winch that withstands up to 1,800 lbs.
- Screw jack for better position.
- **Monochromatic board** in amber color of 3.6x6.2 ft that displays up to 25 different and programmable messages through a windows software in Spanish.
- Cover to protect against inclemency made of 4x2" RHS and 18-gauge black sheet with primary recovering and black enamel.
- **Solar power supply system** through a rechargeable photovoltaic system of 60W-12V-40AH.

WHAT'S A MULTIMESSAGE TRAILER?

This is also known as **Impact Attenuator, Crash Cushion, Towable** or **Trailer Attenuator Arrow Board** and is designed to counter act vehicle impact, resist environment and UV rays; energy absorber (bumper) in black color, improving night visibility as 6 rear marker lights, indicating stop, reverse or turn, inner electronic wire.

it's conformed by various Vitemflex® layers, with an special feature to be integrated by millions of encapsulated air hollows that absorb the vehicle impact, cushioning it; it doesn't damage vehicles due to the energy distribution.



MULTIMESSAGE TRAILER

Sequence Trailer

Code: RE-MUL

TECHNICAL SPECIFICATIONS

TOW

- 2.5" SHS
- Galvanized SHS of 1.5"; 1 1/4" x 1/8" angle
- 16-gauge 4" x 8" galvanized sheet

Manufactured in

Color

- Yellow

Measurements

- TMA of 7.8 ft x 8.5 ft

Suspension

- Leaf Spring System

Support

- Axle of 1,500 lbs

Winch

- 1,800 lbs

ENERGY ABSORBER (BUMPER)

Manufactured in

- Vitemflex ®

Measurements

- Length: 7.9 ft
- Height: 33.0 in
- Width: 29.5 in

ARROW BOARD

Manufactured in

- 18-gauge black sheet, 4" x 2" RHS

Measurements

- Length: 6.2 ft
- Height: 3.6 ft
- Width: 3.9 in

Total Weight

- Approx. 198 lbs

Power Supply

- 12 volts

