

VITEMFLEX 75 DELINEATOR POST

Code: ITO-VF-75

WHAT'S A DELINEATOR POST?

Is considered a signal to prevent or warn people; flexible post specially used to demarcate or sign danger zones and delineate areas, improving visibility in certain risk places.


The main function of this device is avoid vehicles invade prohibited zones, it also delimit roads safely.

It is suggested to use in groups, impeding vehicles park in crosswalks or invade risk zones.



FEATURES

- 2 sizes: 75 (29.5") and 50 cm (19.6") of height.
- 100 % flexible and resistant to impact of vehicles.
- Returns to its original position after collision.
- Withstand multiple run overs.
- Manufactured in Vitemflex®, ductile material that doesn't cause damage to vehicles.
- This post is built according to the standard UNE 135363:98 relating to road delineators.
- It has an upper hole to insert the washer.
- Line color: yellow for greater visibility (other colors upon request).
- 2 prismatic reflective rings to be more visible at night.
- Easy to place or change its position.
- Safe floor anchoring through 1 delineator post, creating a more stable position and a device hard to pull up.
- PVC hexagonal base (optional).



VITEMFLEX 75 DELINEATOR POST

Code: ITO-VF-75

MEASUREMENTS

Dimensions and other measures are nominal and may vary by +/- 2%.

| | Without Base | | | With Base | | |
|--------------|--------------|--------|---------|-----------|---------|-----------|
| | Height | Ø | Weight | Height | Ø | Weight |
| VF-50 | 19.6 in | 4.7 in | 17.6 oz | 20.6 in | 12.5 in | 4,008 lbs |
| VF-75 | 29.5 in | 7.2 in | 2.2 lbs | 30.5 in | 19.6 in | 9,616 lbs |

Color of Reflective Tape • White

ANCHORING

1. Mark the boreholes to position the post with the help of a drill and a 3/8" drill bit for concrete.
2. Drill to a 7" depth, insert the extralarge anchors in every borehole.
3. Mount the delineator post with its 3/8" washer, screw/flat washer,
4. Use a 9/16" socket wrench joined to a "T", going through the post, turn the screw to your right until is tightened enough and...

DONE!

-  21 v Ø 3/8" x 5.9" Hex Head Ultrafix Screw
-  Flat Washer
-  Inner washer inside the post
-  Ø 0.7 in x 5.3 in Extralarge Anchor
-  Borehole in concrete

