

REGULATORY SIGNS

FEATURES



- Regulatory signs and affixed boards with symbols and/or captions used to indicate users in both, rural and urban zones, the existence of physical limitations or restrictions to regulate transit.
- Boards with different shapes as circular, square or even triangular, some examples are R1-1 STOP (SR-6 ALTO), R1-2 YIELD (SR-7a CEDA EL PASO), and some others.
- Signs require complementary information with an additional board in rectangular shape with round borders to create a group or set.
- Board includes a caption to specify the restrictions according to the represented situation.
- Regulatory Signs are classified in **7 groups**:
 - **1:** These are used to regulate the right of way at an intersection without traffic lights.
 - **2:** Used to limit vehicle transit due to circumstantial variations or physical restrictions of the road.
 - **3:** Establish the possibility or enforceability of a movement or action to certain groups of users.
 - **4:** Used to establish the use exclusivity of the road or part of it for certain users.
 - **5:** These forbid a movement or action to some users or group of users.
 - **6:** Used to ban transit to certain users or vehicles. When referring to pedestrians or more than one vehicle type, these can be set in one plate.
 - **7:** Provide complementary information to signs.

REGULATORY SIGNS

TECHNICAL SPECIFICATIONS

Board	16-gauge galvanized sheeting with square shape, except for STOP in octagonal shape and YIELD in triangular shape, with a perimeter board of 1" width, surface free from dusts, clamping plate of 14-gauge galvanized sheeting; with oval drilling at the center, according to the SCT (Secretary of Communications and Transport) specifications, dimensions depend on the project needs.
Background	Engineer grade, high intensity or diamond grade reflective film in white color, except for STOP sign with background in orange color, adhered to sheeting by mechanical resources from 41°F to 77°F, without air bubbles. Back of the board is galvanized.
Sign	The ring and strip in engineer grade, high intensity, diamond or electrocut reflective in red color. For symbols, characters and fillets is in matt black vinyl, except for STOP sign with letters and fillet in white, the YIELD sign has fillet in red color and letters in black, adhered to reflective sheeting by mechanical resources from 41°F to 77°F temperature, without air bubbles.
Post	16-gauge galvanized 2" x 2" RHS with necessary length to reach the required height, complying with the established information on the Manual of Signaling and Traffic Control Devices for Streets and Highways of the SCT.
Screws	For RHS post with 2 1/2" x 3/8" of diameter; nut, flat washer and galvanized lockwasher.

REGULATORY SIGNS

MEASUREMENTS

Dimensions and other measures are nominal and may vary by + / - 2%.

Speed	Size of Regulatory Sign	Captions and Pictograms	Additional Board (in)
	11.8 x 11.8	1	11.8 x 3.9
		2	11.8 x 5.9
		3	11.8 x 7.8 in
<_ 0,30	17.7 x 17.7	1	17.7 x 5.9
		2	17.7 x 88.5
		3	17.7 x 11.8
<_ 40	23.6 x 23.6	1	23.6 x 7.8
		2	23.6 x 11.8
		3	23.6 x 15.7
<_ 60	29.5 x 29.5	1	29.5 x 9.8
		2	29.5 x 147.6
		3	29.5 x 19.6
<_ 90	35.4 x 35.4	1	35.4 x 11.8
		2	35.4 x 17.7
		3	35.4 x 23.6
>90	47.2 x 47.2	1	47.2 x 15.7
		2	47.2 x 23.6
		3	47.2 x 31.4



In urban and interurban roads, the lower part of the sign board is 8.2 ft above the level of the sidewalk or shoulder.

REGULATORY SIGNS

Global Forte Sign Version

FEATURES

- Exclusive board with exceptional measurements that fusion sign with additional board.
- These signs are boards fasten to posts.
- Lightweight body, manufactured in black polyethylene, designed in one piece with one face.
- Resistance to inclemency and temperature changes.
- UV protection.
- Anti-humidity, 100% recyclable.
- Long life span due it doesn't rusts.
- Vandal-proof due is made of plastic, with negligible resale value, avoiding thefts.
- Stackable, reducing transportation and storage costs.
- 2" x 2" plastic post with inner reinforcing, option with round post of 3" diameter.
- Subjected to 176°F test.
- Easy installation.
- **Sign:** prismatic reflective background in white color, text and fillet in black vinyl, ring in red color.

Note: can be **CUSTOMIZED** with institution logo in digital printing if desired.

MEASUREMENTS

Dimensions and other measures are nominal and may vary by + / - 2 %.

General Measurements

- Length: 25.1 in
- Width: 2.4 in
- Height: 31.4 in

Sign Dimensions:

- Length: 23.6 in
- Height: 29.9 in

Reflective Sheeting:

- Prismatic



Height

In urban and interurban roads, the lower part of the sign board is 8.2 ft above the level of the sidewalk or shoulder.

