



GLOBAL FORTE SIGN 71

Code: SE-BA-7171



Comply with NOM-034-SCT2/SEDATU-2022

FEATURES

- Signage boards designed according with 034 SCT2 standard to guarantee visibility and compliance with traffic regulations.
- Integrates latest generation LEDs, maximizing visibility.
- Set on Posteflex® that guarantees resistance to adverse climate conditions, includes grips of black polyethylene and screws for safe fastening.
- Optimal size for an easy recognition at distance of the signs.
- In addition, board can turn 45° and be a warning sign.
- 4 extra LEDs, one per end to increase visibility.
- Type of signs: warning: it warns about possible risks. Restrictive: indicate prohibitions or traffic limitations. Temporary traffic control: inform about works on road. Recreation: sign points of interest and services: Service: indicate available services in the zone. Safety: for emergency situations.
- · IP68 waterproof electronic system.

TECHNICAL FEATURES

- Manufactured in black polymer with one side.
- · Posteflex® in yellow or grey color.
- Resistance to inclemency and temperature changes with UV protection.
- Anti-humidity and recyclable; long life span due it doesn't rust
- Vandal-proof, due is a polymer has zero resale value, neither work for other usages, avoiding thefts.
- Stackable, reducing transport and storage costs.
- Easy installation; Posteflex® with tubular reinforcement on its interior or steel RHS.

SOLAR SYSTEM

- Solar power supply panel on top part.
- LEDs with optics with mirror, causing light expands much better in all the sign.
- 1.2 V batteries.
- JVM power supply electronic circuit that synchronizes flashing of signs at the same time.
- It charges during 5 hours of sun, it lasts 12 hours ON in flashing mode.







Solar cell at top part





GLOBAL FORTE SIGN 71

Code: SE-BA-7171

MEASURES

Dimensions and other measures are nominal and may vary by + - 2 %.

General

- Length: 29.1 in
- Width: 2.7 in
- Height: 29.1 in

Vinyl

- Length: 27.9 in
- Height: 27.9 in

Diamond


- Length: 38.9 in
- Height: 38.9 in

Reflective Sheeting


- According to design
- Width: 1.9 x 1.9 in
- Length: 13.1 ft
- · Thickness: 0.19 in

Posteflex®

- Width: 1.9 x 1.9 in
- Length: 9.8 ft
- Thickness: 0.11 in









POSTEFLEX®

Height

In urban and rural roads, the lower part of the signs stays at 8.2 ft above sidewalk level.

Embed Leave 19

Leave 19.6 in to embed







GLOBAL FORTE SIGN 71

Code: SE-BA-7171

MODES

